



Ionenselektive Elektrode, Ag/S

6.0502.180

Silber- und sulfidselektive Elektrode mit Kristallmembran.

Diese ISE muss in Kombination mit einer Referenzelektrode verwendet werden und eignet sich für:

- Ionenmessungen von Ag^+ (10^{-7} bis 1 mol/L)
- Ionenmessungen von S^{2-} (10^{-7} bis 1 mol/L)
- Ionenmessungen in sehr kleinen Probenvolumina (minimale Eintauchtiefe 1 mm)
- Titrationsen

Dank einem robusten/bruchsicheren Kunststoffschaft aus EP ist dieser Sensor mechanisch sehr belastbar.

Das mitgelieferte Polierset ermöglicht eine einfache Reinigung und Erneuerung der Elektrodenoberfläche.

Lieferumfang 6.0502.180

Qt.	Order no.	Beschreibung
-----	-----------	--------------

1 PCS

6.2802.000

Polishing set for solid-state electrodes

Polishing set with 1 polishing cloth and about 2 g aluminum oxide powder (grain size 0.3 µm)



Optionales Zubehör

Order no.	Beschreibung	
6.0750.100	LL ISE reference electrode	
	Silver / silver chloride reference electrode with double junction system. This reference electrode is well suited for: • automated applications • ion measurements • surfactant titrations The ground-joint diaphragm, which is insensitive to contamination, offers a constant and reproducible electrolyte outflow. Additionally, the reference electrolyte is gelified for even better signal stability. The sensor is delivered with $c(\text{KCl}) = 3 \text{ mol/L}$ as bridge electrolyte, which can be freely selected and exchanged as needed.	
6.2104.020	Electrode cable / 1 m / F	