



PE-Flasche, 125 mL für IC

6.1627.000

Diese Flasche wird in der vollautomatischen Verdünnung eingesetzt.

Optionales Zubehör

Order no.	Beschreibung
6.02743.090	Screw cap with septum

The screw cap with septum is perfectly suitable for maintaining samples and standards over an extended time period. Screw cap with septum for bottle, PP, 50 mL (6.02743.030); PE bottle, 125 ml (6.1627.000) and PE bottle, 50 ml (6.1608.100).

In the case of the 858 Professional Sample Processor, the coated sample needle made of steel (6.2624.200) or the Pick-up needle (6.2624.100) must be mounted in order to penetrate the septum.



6.02743.100 Screw cap without septum, ID 14.2 mm

The screw cap without septum can be used in combination with the bottle PP, 50 mL (6.02743.030). The stopper with perforation (6.2743.070) can be slid into the hole and seals the bottle. This provides a perfect sealing option if the standard needle (6.2846.010) is used on the 858 Professional Sample Processor.



6.9920.255 Sample rack 25 x 60 mL + 10 x 125 mL

Multi-row sample rack for 25 samples in 60 mL Corning® cell culture flasks and 10 samples in 125 mL PE bottles (6.1627.000). Dedicated sample rack for trace analysis, e.g. in power plants.

