



# 728 Magnetic Swing-out Stirrer with stand, 220 V EU

2.728.0034

Incl. 6.2026.010 Base plate and stand rod; incl. 6.2117.020 Power adapter. U = 220...240 V, EU plug.

Below, the accessories are grouped into Scope of delivery and Optional accessories.  
Please keep this printout at hand for ordering replacement material.  
These lists may be subject to change.

## Scope of delivery 2.728.0034

Qt.	Order no.	Description
-----	-----------	-------------

1 PCS

1.728.0010

728 Stirrer without stand

For mounting on a stand rod 10 mm dia.; without base plate (or holder) and without stand rod; without power adapter, with fixed connecting cable.



---

1 PCS

6.1903.030

Stirring bar / 25 mm

Stirring bar with magnetic core, PTFE covering, length 25 mm.



---

1 PCS

6.2013.010

Clamping ring

For support rods with a diameter of 10 mm.



---

1 PCS

6.2026.010

Support stand with support rod

Complete, with stand rod, total length 42 cm. Used with 649, 728 Magnetic Swing-out Stirrer alone (without Dosimat)



Without cable and power plug, with standard cold-devices input socket (C14). Input: 220–240 V AC. For 622, 649, 722, 728 stirrers, 727 Ti Stand or Spectrosense. Output: 9 V DC / 0.2 A.

