

Combined iAg-ring electrode

6.00450.300

Intelligent, combined silver ring electrode with integrated memory chip for storing sensor data. This electrode is suitable for precipitation titrations when the pH value varies (titrant silver nitrate) of, e.g.:

- chloride, bromide, iodide
- sulfides
- hydrogen sulfide
- mercaptans
- cyanides

The fixed ground-joint diaphragm is insensitive to contamination and the permanently fused-in silver ring is resistant to more highly concentrated acids and saline solutions.

 $c(KNO_3) = 1 \text{ mol/L}$ is used as reference electrolyte and storage solution.

Below, the accessories are grouped into Scope of delivery and Optional accessories. Please keep this printout at hand for ordering replacement material. These lists may be subject to change.



Scope of delivery 6.00450.300

Qt.	Order no.	Description	
1 PCS	6.1236.050	Sleeve with SGJ 14/12 mm	
	Sleeve with SGJ 14	l/12 mm, polyethylene.	
1 PCS	6.2008.040	Storage vessel	
	Together with 6.2 the electrode on 8	008.050 storage vessel holder. it provides a support for 07 Dosing Units.	



Optional accessories

Order no.	Description
2.854.0010	854 iConnect
	The 854 iConnect – Electrode cable and measuring amplifier for intelligent "iTrodes" electrodes (cable length 150 cm).
6.2310.010	Electrolyte KNO3-1mol/L 250 mL
	Electrolyte solution KNO_3 1 M (reference electrolyte for combined silver
	electrodes)