

"ProfIC 2 – Anion" – Professional IC System with Inline Ultrafiltration

ProfIC 2 - Anion

The Professional IC system with Metrohm Inline Ultrafiltration and conductivity detection enables the fully automatic determination of anions. "ProfIC 2" enables the safe management of all routine tasks in ion chromatography. It is simple to use and exceptionally reliable.

Schematic diagram

Below, the accessories are grouped into Scope of delivery and Optional accessories. Please keep this printout at hand for ordering replacement material. These lists may be subject to change.

Scope of delivery ProfIC 2 - Anion

Qt. Order no. Description



Compact and intelligent high performance conductivity detector for intelligent IC instruments. Outstanding temperature stability, the complete signal processing within the protected detector block and the latest generation of DSP – Digital Signal Processing – guarantee the highest precision of the measurement. No change of measuring ranges (not even automatic ones) is required, due to the dynamic working range.



1 PCS 2.858.0020 858 Professional Sample Processor – Pump

The 858 Professional Sample Processor – Pump processes samples from 500 μL to 500 mL. The sample transfer takes place either with the installed bidirectional two-channel peristaltic pump or with an 800 Dosino.



Optional accessories

Order no.	Description	
2.800.0010	800 Dosino	
	The 800 Dosino is a drive with write/read hardware for intelligent Do Units. With fixed cable (length 150 cm).	sing T
6.1608.080	Bottle / 300 mL	
	Rinsing vessel for IC Sample Processors.	
6.2041.440	Sample rack 148 x 11 mL + 3 x 300 mL	
	Sample rack for 148 x 11 mL samples with 3 rinsing beakers.	



Sample rack with small diameter for 54 x 11 mL sample vessels in two rows and additionally 1 x 300 mL bottle.

Sample rack $54 \times 11 \text{ mL} + 1 \times 300 \text{ mL}$



6.2041.760

2.5 mL. 2000 pieces. For IC Sample Processors.

The IC sample vessels are made of polypropylene (PP) plastic for health-care applications. Production and packaging both take place under sterile and clean-room conditions (Clean Room Class 7, in accordance with DIN ISO 14644). This guarantees minimal degrees of contamination. The sample vessels are subjected to random checks for leachable anions and cations.



6.2743.050

Sample vessel 11 mL

2000 pieces. For IC Sample Processors and VA Autosamplers.

The IC sample vessels are made of polypropylene (PP) plastic for health-care applications. Production and packaging both take place under sterile and clean room conditions (Clean Room Class 7, in accordance with DIN ISO 14644). This guarantees minimal degrees of contamination. The sample vessels are subjected to random checks for leachable anions and cations.



6.2743.070

Stopper with perforation

2000 pieces. For IC Sample Processors



6.3032.210

807 Dosing Unit 10 mL

807 Dosing Unit with integrated data chip with 10 mL glass cylinder and light protection, mountable to a reagent bottle with ISO/DIN GL 45 glass thread. FEP tubing connection, antidiffusion tip.





Accessories set for mounting a Dosino on intelligent IC instruments for Liquid Handling.



6.5333.000

IQ/OQ Kit for IC

The IQ/OQ Kit contains all parts and standard solutions required for IQ /OQ in ion chromatography.



6.5620.000

Connection set to 807 Dosing Unit: Port 4

For the connection of an M6 tubing to Port 4 on an 807 Dosing Unit (transition from luer to M6), including holder safety device

