



814 USB Sample Processor (1T/2P)

2.814.0020

USB Sample Processor con un puesto de trabajo y dos bombas de membrana integradas para el tratamiento automático de una cantidad pequeña a mediana de muestras rutinarias en serie. Además de las bombas integradas, puede conectarse un máximo de tres dosificadores para tareas de LQH.

Dadas las múltiples variantes de aplicación, la gradilla, los agitadores, el cabezal de titulación, los Swing Head y los recipientes de muestras se deben adaptar a la medida de la aplicación y solicitarse por separado.

El control se efectúa de forma "independiente" mediante Touch Control. Para el control con PC se puede elegir de entre la siguiente selección de productos de software: el software de titulación tiamo™, el software de cromatografía MagIC Net, el software de voltamperometría viva, u OMNIS.

Partes/accesorios 2.814.0020

Qt.	Order no.	Descripción
-----	-----------	-------------

1 PCS

1.814.0020

814 USB Sample Processor (1T/2P)

USB Sample Processor with one workstation and two built-in membrane pumps for the automatic processing of routine samples in series with small to medium quantities. In addition to the built-in pumps, up to three dosing devices for Liquid Handling tasks can be connected.

Because of the multitude of application variants, rack, stirrer, titration head, Swing Head and sample vessels must be tailored to the application and ordered separately.



2 PCS

6.1236.020

Sleeve with SGJ 14/12 mm

Sleeve with SGJ 14/12 mm and O-ring.



5 PCS

6.1446.000

SGJ stopper / B-14/(15)



3 PCS

6.1446.010

Stopper

Used with Sample Changers



1 PCS

6.1446.160

Thermometer stopper, B-14/15, oblique insertion

To have the inserts of the 6.1458.010 titration head in a sloping position.



1 PCS

6.1543.170

Aspiration tip / M8 thread

Aspiration tip for the Sample Processors.



2 PCS

6.1621.000

Container 10 L

As rinsing or waste container in automated systems.



1 PCS

6.1805.110

FEP tubing / M6 / 80 cm

With light and kink protection



3 PCS

6.1805.420

FEP tubing / M6 / 48 cm

With light and kink protection



1 PCS

6.1805.510

PTFE tubing / M8 / 60 cm

With protection against kinks.



2 PCS

6.1812.000

PTFE tubing 4 mm / 6 mm / 4 m



1 PCS

6.1820.070

Coupling 4 mm / 6 mm / M8 inner

For extending aspiration tubing in automated systems. Connects the M8 aspiration tubing directly to the 6.1812.000 PTFE tubing.



2 PCS 6.1828.000 PVDF connection nipple

For 6.1621.000 canister.



1 PCS 6.2053.000 Cable clip

Cable clip for fastening cables and tubes



1 PCS 6.2151.000 Cable USB A – mini-DIN 8-pin

Controller cable



1 PCS 6.2621.030 Hexagon key 4 mm



1 PCS

6.2621.070

5 mm hex key for IC Sample Processors



1 PCS

6.2621.140

Hexagon key 2.5 mm



3 PCS

6.2709.070

Guiding sleeve

For fixation of buret and dosing tips in titration heads and electrode holders



3 PCS


6.2740.020

Spray nozzle


For the fine-spraying of the rinsing solution.



Safety shield for single-tower Sample Processors without 786 Swing Head.



Accesorios opcionales

Order no.	Descripción	
2.741.0010	741 Magnetic Stirrer	
	Magnetic stirrer for sample changers.	
	The magnetic stirrer is located beneath the sample rack.	
2.802.0020	802 Stirrer for sample changer	
	Rod stirrer for sample changer and Sample Processor.	
	With 104 mm 6.1909.020 stirring propeller and permanently installed cable.	
2.849.0010	849 Level Control	
	Additional equipment for Sample Processors for monitoring the filling level of rinsing or waste canisters via Remote. Prevents pumps from running dry and/or canisters from overflowing and is suitable for use with aqueous solutions, solvents and suspensions.	

License-based PC program for controlling complex OMNIS analysis systems.

- Sample-oriented operating procedures with numerous templates
- Graphical method editor with numerous templates
- Clearly organized and professional sample lists
- Management of instruments, work systems, sensors, solutions
- Dialog languages: German, English, Chinese



Enables stand-alone operation of the OMNIS software on a Windows™ computer.

Features:

- The license already includes one OMNIS instrument license.
- Must be activated via the Metrohm licensing portal.
- Not transferable to another computer.



With 6xSGJ 14 and 3x SGJ 9 openings.



6.1458.020 Titration head / 4 x M10 connectors

With 4 M10 screw nipples, including stoppers.



6.1458.030 KF titration head / 4 x M10 connectors

With 4 M10 screw nipples, including stoppers.



6.1458.040 Titration Head, 3 x SGJ 14

Titration head for 120 mL beakers. With 3 openings SGJ 14 and 4 openings 6.4 mm, 2 dosing tips included. Suitable for rinsing and aspiration equipment.



6.1458.070 Titration head / 2 x SGJ 14

Titration head for 75 mL beakers. With 2 openings SGJ 14, 2 openings 6.4 mm, and 3 pre-mounted dosing tips. Suitable for rinsing and aspiration equipment.



6.2041.310 Sample rack, 12 x 250 mL, (PVC)

Sample rack for 810 Sample Processor, 814 USB Sample Processor, 855 Robotic Titrosampler "Light", suitable for 12 sample beakers. The following sample beakers can be used: 6.1432.320, 6.1432.323, 6.1453.220, 6.1453.250.

Plastic: Polyvinyl chloride (PVC)



6.2041.320 Sample rack, 16 x 150 mL, (PVC)

Sample rack for 810 Sample Processor, 814 USB Sample Processor, 855 Robotic Titrosampler "Light", suitable for 16 sample beakers. The following sample beakers can be used: 150 mL beaker (tall).

Plastic: Polyvinyl chloride (PVC)



6.2041.340 Sample rack, 24 x 75 mL, (PVC)

Sample rack for 810 Sample Processor, 814 USB Sample Processor, 855 Robotic Titrosampler "Light", suitable for 24 sample beakers. The following sample beakers can be used: 6.1432.210, 6.1459.400.

Plastic: Polyvinyl chloride (PVC)



6.2041.360 Sample rack, 12 x 150 mL (PVC)

Sample rack for 810 Sample Processor, 814 USB Sample Processor, 855 Robotic Titrosampler "Light", suitable for 12 sample beakers. The following sample beakers can be used: 150 mL beaker (tall), 6.1459.310.


Plastic: Polyvinyl chloride (PVC)



6.2041.370 Sample rack, 14 x 200 mL, (PVC)

Sample rack for 810 Sample Processor, 814 USB Sample Processor, 855 Robotic Titrosampler "Light", suitable for 14 sample beakers. The following sample beakers can be used: 6.1459.310.

Plastic: Polyvinyl chloride (PVC)



6.2041.380 Sample rack, 14 x 235 mL (PVC)

Sample rack for 810 Sample Changer, 814 USB Sample Processor, 855 Robotic Titrosampler "Light", suitable for 14 sample beakers. The following sample beakers can be used: 235 mL (8 oz).

Plastic: Polyvinyl chloride (PVC)



6.2041.390 Sample rack, 16 x 100 mL, (PVC)

Sample rack for 810 Sample Changer, 814 USB Sample Processor, 855 Robotic Titrosampler "Light", suitable for 16 sample beakers. The following sample beakers can be used: 100 mL beakers, short.

Plastic: Polyvinyl chloride (PVC)



6.2041.460 Sample rack, 21 x 100 mL, (PVC)

Sample rack for 810 Sample Processor, 814 USB Sample Processor, 855 Robotic Titrosampler "Light" suitable for 21 sample vessels. The following sample vessels can be used: 100 mL digestion tubes (CSB).

Plastic: Polyvinyl chloride (PVC)



6.2041.470 Sample rack, 22 x 120 mL, (PP)

Sample rack for 810 Sample Changer, 814 USB Sample Processor, 855 Robotic Titrosampler "Light", suitable for 22 sample beakers. The following sample beakers can be used: 6.1459.300, 6.1459.307.

Plastic: Polypropylene (PP)



6.2041.780 Sample rack 65 x 11 mL + 25 x 50 mL

Multi-row sample rack for 65 samples in 11 mL sample vessels (6.2743.050) and 25 samples in 50 mL sample vessels (6.02743.030)



6.2058.110 Tower extension for Sample Processors

Height extension 130 mm for Sample Processors. Tower extension for COD applications.



6.2148.010 Remote Box MSB

Additional remote interface for the connection of devices that can be controlled via remote lines. With permanently attached cable.



6.2711.060

Drip pan for 778/810/814/838/858 Sample Processors

Drip pan for 778, 810, 814, 838, 858 Sample Processors

