



917 Coulometer con electrodo generador con diafragma

2.917.0010

El 917 Coulometer es un titulador compacto para la determinación coulométrica del contenido de agua según Karl Fischer. "Reducido al máximo" –el módulo de manejo, el agitador y la bomba para el rápido recambio de reactivo están integrados en el 917 Coulometer. Esto permite ahorrar mucho espacio en la mesa del laboratorio.

Gama de medida recomendada: 10 µg...200 mg de agua absoluta

La coulometría es el método ideal para la determinación del contenido de agua de líquidos, sustancias sólidas y gases. Además, la coulometría es un método absoluto, por lo que la determinación del título no es necesaria.

Ahora el 917 Coulometer también cumple con la norma FDA 21 CFR, parte 11. Así siempre realizará las auditorías de forma segura.

Partes/accesorios 2.917.0010

Qt.	Order no.	Descripción
-----	-----------	-------------

The 917 Coulometer is a compact titrator for coulometric water determination according to Karl Fischer. "Reduced to the max" – operating module, stirrer and pump are integrated in the 917 Coulometer for rapid reagent replacement. This saves a great deal of space on the laboratory table.



Recommended measuring range: 10 µg...200 mg absolute water
Coulometry is the ideal method for the determination of trace water in liquids, solids and gases. In addition, coulometry is an absolute method and thus no titer determination is necessary.

Indicator electrode used for coulometric Karl Fischer titration.



Generator electrode with diaphragm for coulometric Karl Fischer titrations, SGJ 29/22.

This generator electrode is well suited for:

- samples with very low absolute water contents < 50 ppm
- coulometric water content determination in oil samples
- applications where ketone reagents are used
- applications where low-conducting reagents are used (addition of chloroform, xylene >10%)



For KF coulometers.



1 PCS

6.1437.000

SGJ stopper SGJ 14



1 PCS

6.1439.010

KF addition and aspiration tube

KF addition and aspiration tube for coulometer cell, incl. M8 screw connector 6.1811.010.



2 PCS

6.1446.040

Threaded stopper / M6



1 PCS

6.1446.090

Stopper / B-14/15 / M8



2 PCS 6.1448.020 Septum 16 mm, 5 pieces
Set of 5 pcs.



1 PCS 6.1464.320 KF titration vessel / 80-250 mL / coulometric



2 PCS 6.1602.105 Bottle attachment / GL 45 / green

For direct dosing from reagent bottles with GL 45 thread.



1 PCS 6.1608.023 Amber glass bottle / 1000 mL / GL 45

For Exchange Units. Bottle for auxiliary solutions.



1 PCS

6.1608.030

Round glass bottle / 1000 mL / GL 45



1 PCS

6.1609.010

Adsorber tube with tubing nipple

Lid with tubing nipple.



1 PCS

6.1623.000

Bottle cap overflow protection

Bottle cap overflow protection for 1 waste bottle, prevents the waste bottle from overflowing when an aspiration pump is used



1 PCS

6.1801.120

PVC tubing / 4 mm / 6 mm / 2 m





1 PCS

6.1808.050

Tubing adapter olive / M8 outer

1 M8 outer thread and 1 tubing olive. E.g. for thermostat jacket of exchange units and stability measuring instruments.



1 PCS

6.1819.030

Tube

For M8 threaded holes. For 6.1602.1XX bottle attachments and 6.1608.0XX bottles



1 PCS

6.1819.050

Tube

For M8 threaded holes of 6.1602.10X Bottle attachments with 6.1608.030 Aspiration bottle. For 703 and 803 Ti Stand, 681 Pump Unit and 679 Rancimat



1 PCS

6.1903.030

Stirring bar / 25 mm

Stirring bar with magnetic core, PTFE covering, length 25 mm.



1 PCS

6.2023.020

Clip for SGJ 14/15

Clip for SGJ 14/16



1 PCS

6.2047.040

Titration vessel holder for 899/917

Titration vessel holder for coulometric cells for 899 Coulometer and 917 Ti-Touch



1 PCS

6.2104.020

Electrode cable / 1 m / F

For connecting electrodes with Metrohm plug-in head G to Metrohm instruments (socket F).



1 PCS

6.2104.120

Electrode cable / 1 m / H

With plug H. For connecting generator electrode - KF Coulometer.



1 PCS

6.2164.010

Power supply unit 100 - 240 V/24 V DC

Power supply unit for 915 KF Ti-Touch, 916 Ti-Touch, 917 Coulometer and all Eco Titrators / Eco Dosimat.



1 PCS

6.2701.040

GL 18 screw cap with hole

Made of PBT. With a hole for the 6.1448.020 septum. For the 6.5405.000 cell without diaphragm and the 6.1464.32X and 6.1465.320 titration vessels.



3 PCS

6.2713.000

PTFE sleeve SGJ14

For fat-free ground-joint connection with the standard ground-joint SGJ 14.



1 PCS

6.2713.010

PTFE sleeve SGJ29

Sleeve for fat-free ground-joint connection with the standard ground-joint SGJ 29.



1 PCS

6.2713.020

PTFE sleeve SGJ19

For fat-free ground-joint connection with the standard ground-joint SGJ 19.



1 PCS

6.2738.000

Funnel

For the KF coulometer.



1 PCS

6.2739.000

Wrench

For tightening connectors



1 PCS

6.2811.000

Molecular sieve

Molecular sieve. Bottle containing 250 g. Pore size: 0.3 nm. Without moisture indicator. For Rancimats and Karl Fischer instruments.



2 PCS

6.2816.030

Needle with Luer connector

Needle for filling in mercury into the Multi-Mode Electrode and for sample addition in Karl Fischer titration.



2 PCS

6.2816.090

Syringe 5 mL

5 mL syringe made of PP, with Luer connector.



1 PCS

6.6066.000

USB flash drive for Ti-Touch

USB flash drive for 915 KF Ti-Touch and 916 Ti-Touch.



Accesorios opcionales

Order no.	Descripción
2.142.0100	Custom Q3X thermal printer
	Compact printer with USB interface for
	• 900 Touch Control • 915 KF Ti-Touch • 916 Ti-Touch • 917 Coulometer • 877 / 848 Titrino plus • 865 / 876 Dosimat plus • 91X Meter (cable 6.2151.140) • Eco Dosimat / Titrator • 862 Compact Titrosampler • 870 KF Titrino plus • 899 Coulometer
	Paper width 60 mm (40 characters). Including 6.2151.120 USB cable.



2.143.0200	TX-900MH impact printer
	Compact impact printer with USB and RS232 interface for

- 900 Touch Control (+)
- 915 KF Ti-Touch (+)
- 916 Ti-Touch (+)
- 917 Coulometer (+)
- 91X Meter (+)
- Eco Dosimat/Titrator (+)
- 877/848 Titrino plus (additional 6.2151.100 required)
- 865/876 Dosimat plus (additional 6.2151.100 required)
- 862 Compact Titrosampler (additional 6.2151.100 required)
- 870 KF Titrino plus (additional 6.2151.100 required)
- 899 Coulometer (additional 6.2151.100 required)



(+) Cable included in scope of delivery

6.2723.300

Protective cover for 900 Touch Control

Protective cover for 900 Touch Control

