



814 USB Sample Processor (2T/2P)

2.814.0110

USB Sample Processor avec deux postes de travail et deux pompes à membrane intégrées pour un traitement automatique des échantillons de routine en série, en petit à moyen nombre. En plus des pompes intégrées, il est possible de raccorder deux autres pompes (à membrane ou péristaltiques) ainsi que jusqu'à trois burettes pour les tâches de manipulation des liquides (LQH).

En raison du grand nombre des variantes d'applications, le rack, l'agitateur, la tête de titrage et la Swing Head, ainsi que les récipients d'échantillon, sont conçus spécifiquement pour chaque application et doivent donc être commandés séparément.

Le Touch Control permet un contrôle en « stand alone ». Pour un contrôle par le biais d'un PC, les produits logiciels suivants sont disponibles : le logiciel de titrage tiamo™, le logiciel de chromatographie MagIC Net, le logiciel de voltampérométrie viva ou OMNIS.

Contenu de la livraison 2.814.0110

Qt.	Order no.	Description
-----	-----------	-------------

USB Sample Processor with two workstations and two built-in membrane pumps for the automatic processing of routine samples in series with small to medium quantities. In addition to the built-in pumps, two additional pumps (membrane or peristaltic) and up to three dosing devices for Liquid Handling tasks can be connected.

Because of the multitude of application variants, rack, stirrer, titration head, Swing Head and sample vessels must be tailored to the application and ordered separately.



Sleeve with SGJ 14/12 mm and O-ring.



Used with Sample Changers



2 PCS

6.1621.000

Container 10 L

As rinsing or waste container in automated systems.



2 PCS

6.1805.110

FEP tubing / M6 / 80 cm

With light and kink protection



6 PCS

6.1805.420

FEP tubing / M6 / 48 cm

With light and kink protection



2 PCS

6.1812.000

PTFE tubing 4 mm / 6 mm / 4 m



2 PCS 6.1828.000 PVDF connection nipple

For 6.1621.000 canister.



2 PCS 6.2053.000 Cable clip

Cable clip for fastening cables and tubes



1 PCS 6.2151.000 Cable USB A – mini-DIN 8-pin

Controller cable



1 PCS 6.2621.030 Hexagon key 4 mm



1 PCS

6.2621.070

5 mm hex key for IC Sample Processors



1 PCS

6.2621.140

Hexagon key 2.5 mm



6 PCS

6.2709.070

Guiding sleeve

For fixation of buret and dosing tips in titration heads and electrode holders



6 PCS


6.2740.020

Spray nozzle


For the fine-spraying of the rinsing solution.



Safety shield for dual-tower Sample Processors without 786 Swing Head



Accessoires optionnels

Order no.	Description	
2.741.0010	741 Magnetic Stirrer Magnetic stirrer for sample changers. The magnetic stirrer is located beneath the sample rack.	
2.772.0120	772 Pump Unit – aspirate Peristaltic pump for direct connection to Sample Processors. The "Aspiration" version contains extensive accessories for the aspiration of titrated-out solutions.	
2.802.0020	802 Stirrer for sample changer Rod stirrer for sample changer and Sample Processor. With 104 mm 6.1909.020 stirring propeller and permanently installed cable.	
2.823.0020	823 Membrane Pump Unit «aspirate» Membrane pump for direct connection to Sample Processors. The «Aspiration» version contains numerous accessories for aspirating off solutions.	

2.849.0010

849 Level Control

Additional equipment for Sample Processors for monitoring the filling level of rinsing or waste canisters via Remote. Prevents pumps from running dry and/or canisters from overflowing and is suitable for use with aqueous solutions, solvents and suspensions.



6.06000.000

OMNIS Software storage device

License-based PC program for controlling complex OMNIS analysis systems.

- Sample-oriented operating procedures with numerous templates
- Graphical method editor with numerous templates
- Clearly organized and professional sample lists
- Management of instruments, work systems, sensors, solutions
- Dialog languages: German, English, Chinese



6.06003.010

OMNIS Stand-Alone license

Enables stand-alone operation of the OMNIS software on a Windows™ computer.

Features:

- The license already includes one OMNIS instrument license.
- Must be activated via the Metrohm licensing portal.
- Not transferable to another computer.



6.1458.010 Titration head, 6 x SGJ 14 and 3 x SGJ 9 openings.

With 6xSGJ 14 and 3x SGJ 9 openings.



6.1458.020 Titration head /4 x M10 connectors

With 4 M10 screw nipples, including stoppers.



6.1458.030 KF titration head /4 x M10 connectors

With 4 M10 screw nipples, including stoppers.



6.1458.040 Titration Head, 3 x SGJ 14

Titration head for 120 mL beakers. With 3 openings SGJ 14 and 4 openings 6.4 mm, 2 dosing tips included. Suitable for rinsing and aspiration equipment.



Titration head for 75 mL beakers. With 2 openings SGJ 14, 2 openings 6.4 mm, and 3 pre-mounted dosing tips. Suitable for rinsing and aspiration equipment.



Sample rack for 810 Sample Processor, 814 USB Sample Processor, 855 Robotic Titrosampler "Light", suitable for 12 sample beakers. The following sample beakers can be used: 6.1432.320, 6.1432.323, 6.1453.220, 6.1453.250.

Plastic: Polyvinyl chloride (PVC)



Sample rack for 810 Sample Processor, 814 USB Sample Processor, 855 Robotic Titrosampler "Light", suitable for 16 sample beakers. The following sample beakers can be used: 150 mL beaker (tall).

Plastic: Polyvinyl chloride (PVC)



Sample rack for 810 Sample Processor, 814 USB Sample Processor, 855 Robotic Titrosampler "Light", suitable for 24 sample beakers. The following sample beakers can be used: 6.1432.210, 6.1459.400.


Plastic: Polyvinyl chloride (PVC)



6.2041.360 Sample rack, 12 x 150 mL (PVC)

Sample rack for 810 Sample Processor, 814 USB Sample Processor, 855 Robotic Titrosampler "Light", suitable for 12 sample beakers. The following sample beakers can be used: 150 mL beaker (tall), 6.1459.310.


Plastic: Polyvinyl chloride (PVC)



6.2041.370 Sample rack, 14 x 200 mL, (PVC)

Sample rack for 810 Sample Processor, 814 USB Sample Processor, 855 Robotic Titrosampler "Light", suitable for 14 sample beakers. The following sample beakers can be used: 6.1459.310.

Plastic: Polyvinyl chloride (PVC)



6.2041.380 Sample rack, 14 x 235 mL (PVC)

Sample rack for 810 Sample Changer, 814 USB Sample Processor, 855 Robotic Titrosampler "Light", suitable for 14 sample beakers. The following sample beakers can be used: 235 mL (8 oz).

Plastic: Polyvinyl chloride (PVC)



6.2041.390 Sample rack, 16 x 100 mL, (PVC)

Sample rack for 810 Sample Changer, 814 USB Sample Processor, 855 Robotic Titrosampler "Light", suitable for 16 sample beakers. The following sample beakers can be used: 100 mL beakers, short.

Plastic: Polyvinyl chloride (PVC)



6.2041.460 Sample rack, 21 x 100 mL, (PVC)

Sample rack for 810 Sample Processor, 814 USB Sample Processor, 855 Robotic Titrosampler "Light" suitable for 21 sample vessels. The following sample vessels can be used: 100 mL digestion tubes (CSB).

Plastic: Polyvinyl chloride (PVC)



6.2041.470 Sample rack, 22 x 120 mL, (PP)

Sample rack for 810 Sample Changer, 814 USB Sample Processor, 855 Robotic Titrosampler "Light", suitable for 22 sample beakers. The following sample beakers can be used: 6.1459.300, 6.1459.307.

Plastic: Polypropylene (PP)



6.2041.780 Sample rack 65 x 11 mL + 25 x 50 mL

Multi-row sample rack for 65 samples in 11 mL sample vessels (6.2743.050) and 25 samples in 50 mL sample vessels (6.02743.030)



6.2058.110 Tower extension for Sample Processors

Height extension 130 mm for Sample Processors. Tower extension for COD applications.



6.2141.300

Remote cable 843 Pump Station to Sample Processor

Remote cable for the direct connection of the 843 Pump Station to the pump connectors of the Sample Processors



6.2148.010

Remote Box MSB

Additional remote interface for the connection of devices that can be controlled via remote lines. With permanently attached cable.



6.2711.060

Drip pan for 778/810/814/838/858 Sample Processors

Drip pan for 778, 810, 814, 838, 858 Sample Processors

