



Titrages coulométriques KF automatisés

MATi 04

MATi 4 est un système entièrement automatisé pour des titrages KF coulométriques avec un débit d'échantillons élevé. Le rack d'échantillons du Sample Processor peut recevoir jusqu'à 160 échantillons en flacons de 6 mL. L'échantillon est pipeté dans une cellule coulométrique externe, où le titrage KF est effectué. Le système est contrôlé par le logiciel OMNIS.

Contenu de la livraison MATi 04

Qt.	Order no.	Description
1 PCS	2.786.0040	786 Swing Head
		Additional equipment for Robotic Sample Processors XL without titration or transfer heads.



1 PCS

2.800.0010

800 Dosino

The 800 Dosino is a drive with write/read hardware for intelligent Dosing Units. With fixed cable (length 150 cm).



1 PCS

2.801.0010

801 Stirrer

Magnetic stirrer without stand for supplementing the Titrino plus, Dosimat plus, Titrandos, Sample Processors, 805 Dosimats and 780/781 pH Meters. With permanently attached cable for MSB (Metrohm Serial Bus).



1 PCS

2.815.0030

815 Robotic USB Sample Processor XL (1T/0P)

Robotic USB Sample Processor XL with one workstation for the automatic processing of routine samples in series with large quantities and for complex sample preparation or parallel runs. Up to two pumps (membrane or peristaltic) and three dosing devices for Liquid Handling tasks can be connected.

Because of the multitude of application variants, rack, stirrer, titration head, robotic arm, Swing Head and sample vessels must be tailored to the application and ordered separately.

The control is "stand alone" using Touch Control. The following software products can be selected for the PC control: tiamo™ titration software, MagIC Net chromatography software, viva voltammetry software, or OMNIS.



Coulometer including generator electrode without diaphragm.

Coulometry is the ideal method for water content determination in liquids, solids, and gases when it comes to water content determination in the trace range (10 µg to 10 mg absolute water). In addition, coulometry is an absolute method and thus no titer determination is necessary.



Coulometric titrations are carried out easily and quickly with the 851 Titrande.

Recommended measuring range: 10 µg - 200 mg absolute water.

For use with OMNIS Software, tiamo software, or Touch Control unit. Compliance with GMP/GLP and FDA regulations such as 21 CFR Part 11, if required.

Generator electrode with diaphragm for coulometric Karl Fischer titrations, SGJ 29/22.

This generator electrode is well suited for:

- samples with very low absolute water contents < 50 ppm
- coulometric water content determination in oil samples
- applications where ketone reagents are used
- applications where low-conducting reagents are used (addition of chloroform, xylene >10%)



License-based PC program for controlling complex OMNIS analysis systems.

- Sample-oriented operating procedures with numerous templates
- Graphical method editor with numerous templates
- Clearly organized and professional sample lists
- Management of instruments, work systems, sensors, solutions
- Dialog languages: German, English, Chinese



1 PCS

6.06003.012

OMNIS stand-alone license with 2 instrument licenses

Enables stand-alone operation of the OMNIS Software on a Windows™ computer.

Features:

- The license already includes two OMNIS instrument licenses.
- Must be activated via the Metrohm licensing portal.
- Not transferable to another computer.




1 PCS

6.1448.050

Aluminum septum caps / 1000 pieces

Including Al sealing.



1 PCS

6.1543.070

Aspiration tip / M6 thread

For the 661 Pump Unit



1 PCS

6.1562.130

Transfer Tubing with holder 2 x M6 / 10 mL to
Sample Processors

Transfer tubing for dilution and preconcentration using a Dosino and
Sample Processor.



1 PCS 6.1805.100 FEP tubing / M6 / 40 cm
With light and kink protection



1 PCS 6.2041.710 Sample rack, 160 x 6 mL, (PVC)

Sample rack for 815 Robotic Sample Processor, 855 Robotic Titrosampler "Basic" suitable for 160 sample vessels. The following sample vessels can be used: 6.2419.000.

Plastic: Polyvinyl chloride (PVC)



1 PCS 6.2151.000 Cable USB A – mini-DIN 8-pin
Controller cable



1 PCS 6.2419.000 Sample glass, 6 mL, 1000 pieces

Sample glass for up to 6 mL sample, suitable for 6.1448.050 septum, 1,000 pieces



1 PCS

6.2621.110

Crimping tongs

Crimping tongs for sealing 6 mL sample vials (6.2419.000, 6.2419.007).



1 PCS

6.3032.210

807 Dosing Unit 10 mL

807 Dosing Unit with integrated data chip with 10 mL glass cylinder and light protection, mountable to a reagent bottle with ISO/DIN GL 45 glass thread. FEP tubing connection, antidiffusion tip.



1 PCS

6.5619.000

Transfer equipment, 0.5 - 2 mL, for 789/815

Complete equipment for the transfer of solutions from 0.5 to 2.0 mL on the Robotic Sample Processor.

