



781 pH/Ion Meter

2.781.0010

Oltre alla misurazione degli ioni, del pH, della tensione e della temperatura, il 781 pH/Ion Meter combinato possiede anche un controllo automatico dell'agitatore, una calibrazione multi-punto con al massimo 9 tamponi (modalità pH), una memoria metodi e varie funzioni di monitoraggio. Il test elettrodo automatico per pH conforme GLP consente la valutazione oggettiva dell'elettrodo. Il grande display a più righe retroilluminato consente una buona visione d'insieme e facilita le impostazioni individuali. L'interfaccia RS232 bidirezionale consente il trasferimento di dati a una stampante o a un PC.

Per la misurazione di ioni sono disponibili tre modalità diverse: misurazione diretta, addizione standard o addizione del campione. Nel caso dell'addizione standard completamente automatica con un Dosimat opzionale, è sufficiente immettere la concentrazione dello standard e il numero desiderato di passi di addizione, al resto ci pensa il pHmetro/ionometro. Per la calibrazione ai fini della misurazione diretta possono essere utilizzati fino a 19 standard.

Parti incluse 2.781.0010

Qt.	Order no.	Descrizione
-----	-----------	-------------

In addition to pH, ion, voltage and temperature measurement, the combined 781 pH/Ion Meter also offers an automatic stirrer control, a multi-point calibration with up to nine buffers (pH mode), a method memory and various monitoring functions. The automatic pH electrode test in conformance with GLP permits objective assessment of the electrode. The large backlit multi-line display provides an overview and makes the individual settings easy. The bi-directional RS-232 interface enables data transfer to a printer or PC.



Three different modes are available for ion measurement: direct measurement, standard or sample addition. In the case of fully automated standard addition with an optional Dosimat, only the concentration of the standard and the desired quantity of addition steps need to be entered, the pH/ion meter takes care of the rest. Up to 19 standards can be used for the calibration for direct measurement.

Combined pH electrode with integrated Pt1000 temperature sensor for pH measurements/titrations. This electrode is particularly suitable:

- for pH measurements and titrations in difficult, viscous, or alkaline samples
- at elevated temperatures
- for long-term measurements




The fixed ground-joint diaphragm is insensitive to contamination.

Reference electrolyte: $c(\text{KCl}) = 3 \text{ mol/L}$, storage in storage solution.

Alternatively: reference electrolyte for measurements at $T > 80^\circ\text{C}$: Idrolyte, storage in Idrolyte.

Support stand for 780, 781 pH meter



1 PCS

6.2013.010

Clamping ring

For support rods with a diameter of 10 mm.



1 PCS

6.2016.070

Support rod / 400 mm



1 PCS

6.2021.020

Electrode holder

Electrode holder for 4 electrodes and 2 buret tips



1 PCS

6.2104.600

Electrode cable for plug in head U/plug F, 2x2 mm B,
1m

For connecting electrodes with Metrohm plug-in head U to Metrohm
instruments (socket F).



1 PCS

6.2153.000

Power adapter 100-240 V / 12 V DC

Power supply, 100-240 V, 50-60 Hz, 12 V DC for 780 pH-/Ionmeter, 781,
is also used with 6.1830.020 heatable tubing



1 PCS

6.2621.070

5 mm hex key for IC Sample Processors



1 PCS

6.2621.130

Hexagon key 2 mm

2 mm.



Accessori opzionali

Order no.	Descrizione	
2.140.0200	Impact printer CUSTOM DP40-S4N Normal paper printer, paper width 58 mm (40 columns), serial interface RS 232C (DB9). U = 100...240 V, 50/60 Hz.	
2.801.0010	801 Stirrer Magnetic stirrer without stand for supplementing the Titrino plus, Dosimat plus, Titrandos, Sample Processors, 805 Dosimats and 780/781 pH Meters. With permanently attached cable for MSB (Metrohm Serial Bus).	
2.802.0040	802 Stirrer for 804 Ti Stand Rod stirrer including 6.1909.010 stirring propeller.	
2.804.0010	804 Ti Stand without stand rod Titration stand and controller for 802 Stirrer. The 804 Ti Stand together with the optional 802 Stirrer provides an alternative to the magnetic stirrer. Without stand.	

Universal dispensing unit for titration and dosing tasks in the laboratory. Including push-button cable for manual dispensing control and 6.3026.220 exchange unit (20 mL). A multitude of instruments can be connected at the USB interface of the Dosimat plus, even a number of them simultaneously when a USB hub is used (keyboard, mouse, USB compact printer or USB DIN A4 printer, USB Memory Stick for methods and data backup). The optional 6.2148.030 USB/RS-232 Adapter Box enables the connection of laboratory balances and operation with a computer.



With its four dosing modes, the Dosimat plus offers a multitude of applications:

DOS (Dosing) – Dosing at the press of a button

This mode is particularly suitable for performing manual titrations with indicator. A result can be calculated and a result report can be printed automatically from the dosed volume.

XDOS (Extended dosing) – Controlled dosing

- Fixed volume dosing: The volume and the dosing rate are specified.
- Time-controlled dosing: The volume and the time are specified.
- Dosing according to dosing rate: The dosing rate and the time are specified.

If continuous dosing without interruption is required, then the 865 Dosimat plus can be operated together with an 805 Dosimat in tandem mode.

CNT D (Content dosing) – Preparation of standard and other solutions.

The volume of the solvent to be dosed is determined automatically on the basis of the sample size of the starting substance (solid or stock solution) and the specified target concentration.

LQT (Liquid transfer) – Pipetting and diluting of liquids.

Universal dispensing unit for manual titrations and dosings. Including push-button cable for manual dosing control and 20 mL exchange unit. A multitude of instruments can be connected at the USB interface of the Dosimat plus, even a number of them simultaneously when a USB hub is used (keyboard, mouse, USB compact printer or USB DIN A4 printer, USB Memory Stick for methods and data backup). The optional 6.2148.030 USB/RS-232 Adapter Box enables the connection of laboratory balances and operation with a computer. With its two dosing modes, the Dosimat plus offers the following applications:



DOS (Dosing) – Dosing at the press of a button

This mode is particularly suitable for performing manual titrations with indicator. A result can be calculated and a result report can be printed automatically from the dosed volume.

XDOS (Extended dosing) – Controlled dosing

- Fixed volume dosing: The volume and the dosing rate are specified.
- Time-controlled dosing: The volume and the time are specified.
- Dosing according to dosing rate: The dosing rate and the time are specified.

6.2103.130

Adapter red 2 mm plug / 4 mm socket

For connecting plug B (4 mm) to 2 mm socket.



6.2103.140

Adapter black 2 mm plug / B socket 4 mm

For connecting plug B (4 mm) to 2 mm socket.



6.2125.090 RS-232 cable 1 m, 25-pin D – sub 25
RS-232 extension cable (1:1). Specially shielded.



6.2125.110 RS-232 cable 3 m, 25-pin – 9-pin
Connecting Metrohm RS-232 interface to PC. Used with pH Meters, Titrinos, KF Coulometers, VA Trace Analyzer.



6.2125.120 Adapter sub D 25-pin/5 sockets
Distributes the «Remote lines to 5 x 25-pin sockets. Used with pH Meters, Titrinos, KF Coulometer, Sample Changers, IC systems, etc.



6.2134.040 RS-232 DB9 - IBM-PC(DB9) connecting cable
For the Metrohm RS-232 interface - PC connection. For Titrinos, Titrino plus and 756, 831 KF Coulometer, RS-232/USB Box



6.2134.110

Cable RS-232 DB9 socket f – DB9 plug

Connecting Metrohm RS-232 interface (DB9) to a Custom DP40 printer.
For Titrinos or 756/831 KF Coulometer. RS-232 extension cable (1:1)



6.2141.320

Remote cable 869 Compact Sample Changer to Remote box MSB


Remote cable (9-pin) for the connection of a 869 Compact Sample
Changer to (6.2148.010). Remote box MSB



6.2141.350

Cable Dosimat Plus (9p) - 781 (25p)

Cable for connection of a Dosimat Plus to 781 pH/Ion meter for standard
addition



6.2148.010

Remote Box MSB

Additional remote interface for the connection of devices that can be
controlled via remote lines. With permanently attached cable.



6.2307.230

Buffer solutions pH 4, 7 and 9

Mixed buffer solutions pH 4.00/7.00/9.00 (25 °C) in single use sachets, colourless, box of 3 x 10 x 30 mL



6.2325.000

pHit kit

Maintenance kit for pH electrodes

The kit contains:

- 50 mL cleaning solution
- 50 mL 3M KCl solution
- 50 mL storage solution
- 2 Storage vessels
- Instructions for use

