

859 Titrotherm

2.859.0010

2.859.0010

Qt.	Order no.		
1 PCS	1.859.0010	Titrotherm	





Controller cable





Order no.

2.800.0010 800 Dosino

The 800 Dosino is a drive with write/read hardware for intelligent Dosing Units. With fixed cable (length 150 cm).



2.802.0040 802 Stirrer for 804 Ti Stand

Rod stirrer including 6.1909.010 stirring propeller.



2.804.0010 804 Ti Stand without stand rod

Titration stand and controller for 802 Stirrer. The 804 Ti Stand together with the optional 802 Stirrer provides an alternative to the magnetic stirrer. Without stand.



6.1414.010 Titration vessel lid with 5 openings





6.2013.010 Clamping ring

For support rods with a diameter of 10 mm.



6.2026.010 Support stand with support rod

Complete, with stand rod, total length 42 cm. Used with 649, 728 Magnetic Swing-out Stirrer alone (without Dosimat)



6.2061.010 Bottle holder for Dosinos

Bottle holder for up to two Dosinos, mounted on 1 L reagent bottles.



6.3032.120 807 Dosing Unit 2 mL

807 Dosing Unit with integrated data chip with 2 mL glass cylinder and light protection, mountable to a reagent bottle with ISO/DIN GL 45 glass thread. FEP tubing connection, antidiffusion tip.



6.3032.150 807 Dosing Unit 5 mL

807 Dosing Unit with integrated data chip with 5 mL glass cylinder and light protection, mountable to a reagent bottle with ISO/DIN GL 45 glass thread. FEP tubing connection, antidiffusion tip.



6.3032.210 807 Dosing Unit 10 mL

807 Dosing Unit with integrated data chip with 10 mL glass cylinder and light protection, mountable to a reagent bottle with ISO/DIN GL 45 glass thread. FEP tubing connection, antidiffusion tip.



6.3032.220 807 Dosing Unit 20 mL

807 Dosing Unit with integrated data chip with 20 mL glass cylinder and light protection, mountable to a reagent bottle with ISO/DIN GL 45 glass thread. FEP tubing connection, antidiffusion tip.





807 Dosing Unit with integrated data chip with 50 mL glass cylinder and light protection, mountable to a reagent bottle with ISO/DIN GL 45 glass thread. FEP tubing connection, antidiffusion tip.



6.9011.020 Thermoprobe

High-sensitivity temperature sensor for thermometric titration with an 859 Titrotherm.

The Thermoprobe has a short response time and a high resolution, which enables the precise recording of even the smallest temperature changes.

This sensor can be used in aqueous and non-aqueous solutions which do not contain any HF, for determinations such as:



- acid number (TAN) in accordance with ASTM D8045
- total base number (TBN)
- · free fatty acids
- Ca /Mg determination
- phosphate

6.9011.040 Thermoprobe HF

High-sensitivity temperature sensor for thermometric titrations with an 859 Titrotherm in HF-containing media.

The Thermoprobe has a short response time and a high resolution, which enables the precise recording of even the smallest temperature changes.

This sensor can be used in acidic, fluoride-containing solutions but is not resistant to organic solvents. It is suitable for:



- the determination of sodium
- · titration of etching baths