



Conductivity measuring cell $c = 0.1 \text{ cm}^{-1}$ with Pt1000 (fixed cable)

6.0918.040

Conductivity measuring cell made of stainless steel with cell constant $c = 0.1 \text{ cm}^{-1}$ (guide value), with integrated Pt1000 temperature sensor and fixed cable for connecting to 912/914 Meters. This sensor is suitable for measurements of low conductivities ($0 \mu\text{S}/\text{cm}$ to $300 \text{ uS}/\text{cm}$) in, e.g. deion. water.

Phạm vi giao hàng 6.0918.040

Qt.	Order no.	Description
1 PCS	6.1236.050	Sleeve with SGJ 14/12 mm Sleeve with SGJ 14/12 mm, polyethylene.



Phụ kiện tùy chọn

Order no.	Description
-----------	-------------

6.1420.100 Flow-through measuring vessel
For 12 mm dia. electrodes (pH, metal, conductivity)



6.2324.010 Conductivity standard 100 $\mu\text{S}/\text{cm}$ 250 mL
Conductivity standard for calibration of conductivity measuring cells with cell constant = 0.1/cm.



6.2324.110 Conductivity standard 100 $\mu\text{S}/\text{cm}$, 5 x 30 mL
Conductivity standard for calibration of conductivity measuring cells with cell constant = 0.1/cm.

