

## IC equipment: Liquid Handling Station, left

6.5330.130

Accessory set for assembling the Liquid Handling Station on the Professional Sample Processor. The rinsing water supply can be accomplished by means of a peristaltic pump or a Dosino.

## Phạm vi giao hàng 6.5330.130

Qt.	Order no.	Description	
1 PCS	6.1014.200	Metrosep I Trap 1 - 100/4.0	
	The Metrosep I Trap 1 - 100/4.0 column is used to eliminate ionic, i.e. cationic and anionic, contaminants from aqueous solutions. Its use is especially recommended for the purification of the transfer water in combination with "MISP" or "Metrohm Inline Sample Preparation". Using the Metrosep I Trap 1 - 100/4.0 column can significantly reduce the influence of the transfer water on the system blank.		



For eluent, reagent, and rinsing bottles, with connectors for the adsorber tube and the aspiration tubing.



1 PCS

6.1608.070

Eluent bottle / 2 L / GL 45



1 PCS

6.1619.000

Adsorber tube for 807 Dosing Unit



1 PCS

6.1624.000

Adapter SGJ 14 for 6.1619.XXX Adsorber tube

 $\label{processor} Adapter\,SGJ\,14.\,Part\,of\,6.1619.010\,for\,Dilution\,Sample\,Processor.$ 





For the sample solution in Inline Ultrafiltration.



1 PCS 6.1831.180 PEEK Capillary 0.5 mm i.d., 3 m

6.1826.390



1 PCS 6.2744.010 Pressure screw 5x

With UNF 10/32 connection. For the connection of PEEK capillaries



1 PCS 6.2744.034 Coupling olive/UNF 10/32, 2x

Connection between pressure screw and pump tubing. 2 pieces. For IC instruments with peristaltic pump.



6.2841.120

Combined rinsing and dilution station for sample changers with a Swing Head. To be assembled to the left of the tower.



