

851 Titrando Touch Control

2.851.0120

Touch Control

10 μg 10 mg

851 Titrando

10 μg - 200 mg

OMNIS-Software tiamo- Touch Control GMP/GLP FDA 21 CFR 11

Scope of delivery 2.851.0120

Qt. Order no. Description



Coulometry is the ideal method for water determination in liquids, solids and gases when it comes to water determination in the trace range (10 µg to 10 mg absolute water). In addition, coulometry is an absolute method and thus no titer determination is necessary.

Coulometric titrations are carried out easily and quickly with the **851 Titrando**.

Recommended measuring range: 10 µg - 200 mg absolute water

1 PCS 1.900.0010 900 Touch Control

Operating unit for the Titrandos, USB Sample Processors, 856 Conductivity Module, 867 pH Module and 846 Dosing Interface. Touch-sensitive, high-resolution color display, simple and intuitive operation, thanks to Favorites for direct method access. With integrated Ethernet interface for direct connection to the Internet and USB interface for connecting USB printers or a USB memory stick.



Dialog languages: German, English, Chinese, French, Spanish, Portuguese, Russian, Korean, Polish and Italian.

1 PCS 6.0341.100 Double Pt-wire electrode for coulometry

Indicator electrode used for coulometric Karl Fischer titration.



1 PCS **6.0345.100 Generator electrode without diaphragm**

Generator electrode without diaphragm for coulometric Karl Fischer titrations, SGJ 29/22. This generator electrode is well suited for most applications where the sample is highly soluble in alcohol.





For KF coulometers.



1 PCS

6.1437.000

SGJ stopper SGJ 14



1 PCS

6.1446.060

Stopper / B-14/15 / M10



2 PCS

6.1448.020

Septum 16 mm, 5 pieces

Set of 5 pcs.





1 PCS **6.1903.030 Stirring bar / 25 mm**

Stirring bar with magnetic core, PTFE covering, length 25 mm.



2 PCS 6.2043.005 Holding clip for bottles

Holding spring for reagent bottles in exchange units.



1 PCS 6.2047.020 Titration vessel holder

Titration vessel holder for coulometric cells. Used with 756, 831 KF Coulometer



1 PCS

6.2104.020 Electrode cable / 1 m / F

For connecting electrodes with Metrohm plug-in head G to Metrohm instruments (socket F).



1 PCS

6.2104.120 Electrode cable / 1 m / H

With plug H. For connecting generator electrode - KF Coulometer.



1 PCS

6.2701.040 GL 18 screw cap with hole

Made of PBT. With a hole for the 6.1448.020 septum. For the 6.5405.000 cell without diaphragm and the 6.1464.32X and 6.1465.320 titration vessels.



3 PCS

6.2713.000

PTFE sleeve SGJ14

For fat-free ground-joint connection with the standard ground-joint SGJ 14.



Sleeve for fat-free ground-joint connection with the standard ground-joint SGJ 29.



1 PCS **6.2713.020 PTFE sleeve SGJ19**

For fat-free ground-joint connection with the standard ground-joint SGJ 19.



1 PCS **6.2730.030 Stopper**

Complete with nipple and O-ring. For 6.1414.030 titration vessel lids. For KF instruments, VA measurement stands, VA Computrace and IC Dilution.



1 PCS **6.2738.000 Funnel**

For the KF coulometer.



Needle for filling in mercury into the Multi-Mode Electrode and for sample addition in Karl Fischer titration.



2 PCS

6.2816.090

Syringe 5 mL

5 mL syringe made of PP, with Luer connector.



1 PCS

6.6064.010

USB Memory Stick for 900 Touch Control



Optional accessories

Order no.	Description
6.2103.130	Adapter red 2 mm plug / 4 mm socket
	For connecting plug B (4 mm) to 2 mm socket.

6.2103.140 Adapter black 2 mm plug / B socket 4 mm

For connecting plug B (4 mm) to 2 mm socket.

