

5 c= 0.7 cm-1 Pt1000

6.0915.100

 $5 c = 0.7 cm^{-1}$ () Pt1000 1.2 m 856 $5 \mu S/cm$ 20 mS/cm

- •
- •

Scope of delivery 6.0915.100

Qt. Order no. Description



Sleeve with SGJ 14/12 mm, polyethylene.



1 PCS 6.2008.040 Storage vessel

Together with 6.2008.050 storage vessel holder. it provides a support for the electrode on 807 Dosing Units.





Optional accessories

Order no.	Description	
6.2301.060	KCI ion standard 250 mL	
	KCI ion standard (c(ion) = 0.1000 +/-0.0005 mol/L), can also be used as	
	standard solution for conductometry 12.87 mS/cm (25 °C).	
		The second of th

6.2324.010 Conductivity standard 100 μS/cm 250 mL

Conductivity standard for calibration of conductivity measuring cells with cell constant = 0.1/cm.



6.2324.110 Conductivity standard 100 μS/cm, 5 x 30 mL

Conductivity standard for calibration of conductivity measuring cells with cell constant = 0.1/cm.



6.2763.000 Flow-through cell for the 6.0915.100/6.0920.100

Flow-through cell for the 6.0915.100/6.0920.100 5-ring conductivity measuring cell

